

MACH ULTIMER FEEDER

Compact In-line Ultimeer feeding system

Description

Excellent cost-effective ultimer feeding system designed for in-line dosing of ultimersolution into your process application.

The Mach Ultimeer feeder works with a forced injection-T which and static mixer produces the required mixed water-ultimer solution.

If needed the unit can run in batch operation mode.

Options

External calibration cylinder with lift pump

Duo filter

High/low – level switch (Batch operation)

Easy installation

Lightweight, flexible construction ensures easy installation, and that saves installation time.

Easy maintenance

All spare parts are easily replaced by a service technician.



Specifications	Micro MACH	Mini MACH	MACH	Maxi MACH
Part No.	MACH-000-000	MACH-100-000	MACH-200-000	MACH-300-000
Water flow (max)	100 l/h	650 l/h	1000 l/h	2500 l/h
Polymer capacity	0,1 - 1 l/h	0,3 - 2 l/h	0,5 - 8 l/h	1 - 25 l/h
Dimensions	800 x 650 x 1350	800 x 650 x 1350	800 x 650 x 1350	800 x 650 x 1350
Min. Water pressure	3,5 Bar	3,5 Bar	3,5 Bar	3,5 Bar
Power supply	230 V, 50 Hz	230 V, 50 Hz	230 V, 50 Hz	230 V, 50 Hz